

# SJIII 4632

## ELECTRIC SCISSOR LIFTS

### STANDARD FEATURES

- SKYCODED™ colour coded and numbered wiring system
- Tilt sensor 1.5 x 3.5
- Drivable at full height
- Variable speed, rear two wheel hydraulic drive
- Wet disc SAHR brakes
- Proportional controls for drive & lift functions
- 0.91 m Roll out extension deck
- 24V DC Power source
- 250 Ah Batteries
- Low voltage battery protection
- 25% Gradeability
- Solid rubber, non-marking tyres
- Pothole protection system
- Wiring for AC outlet on platform
- Tilt alarm with drive & lift cut-out
- All motion audible alarm
- Overload sensing system
- Lowering warning system
- Lanyard attachment points
- Operator horn
- Flashing light
- Half height spring hinged gate
- Hinged railing system
- Forklift pockets and tie down/lift lugs
- Relay based control system

### ACCESSORIES AND OPTIONS

- AGM Batteries
- Dual flashing lights
- Full height spring hinged gate
- Light duty pipe rack
- Heavy duty pipe rack
- Board/drywall carrier
- Tool caddy
- Secondary Guarding Lift Enable (SGLE)
- ELEVATE telematics

# SJIII 4632 ELECTRIC SCISSOR LIFTS

Dimensions	SJIII 4632
<b>A</b> Work Height	11.75 m
<b>B</b> Raised Platform Height	9.75 m
<b>C</b> Lowered Platform Height	1.23 m
<b>D</b> Overall Width	1.17 m
<b>E</b> Overall Length	2.31 m
<b>F</b> Stowed Height (Rails Up)	2.24 m
<b>G</b> Stowed Height (Rails Down)	1.88 m
<b>H</b> Platform Width (Inside Dimension)	1.07 m
<b>I</b> Platform Length (Inside Dimension)	2.13 m
Specifications	SJIII 4632
Extension Deck (Roll Out)	0.91 m
Ground Clearance (Stowed)	8.89 cm
Ground Clearance (Raised)	1.91 cm
Wheelbase	1.75 m
Weight	2,720 kg
Gradeability	25%
Turning Radius (Inside)	1.21 m
Turning Radius (Outside)	2.37 m
Lift Time (With Rated Load)	59 sec
Drive Speed (Stowed)	2.4 km/h
Drive Speed (Raised)	1.1 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	318 kg
Maximum # of Persons (0 Wind Rating)	2
Maximum # of Persons (12.5 m/sec Wind Rating)	1

